

BLANK PAGE



भारतीय मानक

खान टब युग्मन और कर्षण शलाकाएँ

भाग 4 एफ-शैकल और लिंक टाईप

(पहला पुनरोक्षण)

Indian Standard

MINE TUB COUPLINGS AND DRAWBARS

PART 4 F-SHACKLE AND LINK TYPE

(First Revision)

UDC 622·625·24·013

© BIS 1995

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (Part 4) (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Mine Transportation Sectional Committee had been approved by the Heavy Mechanical Engineering Division Council.

This standard on mine tub couplings is one of the series of standards on mine tub couplings. Other parts of this standard are:

IS 8534 (Part 1): 1994	Mine tub couplings and drawbars: Part 1 General requirements (first revision)
IS 8534 (Part 2): 1995	Mine tub couplings and drawbars: Part 2 C-link and D-shackle type (first revision)
IS 8534 (Part 3): 1995	Mine tub couplings and drawbars: Part 3 R-shackle and link type (first revision)
IS 8534 (Part 5): 1995	Mine tub couplings and drawbars: Part 5 Drawbars
IS 8534 (Part 6): 1995	Mine tub couplings and drawbars: Part 6 Hook and D-shackle type

This standard (Part 4) was first published in 1977. It was covering requirements of bow shackle type coupling which could be used with special drawbars and not on the drawbars having D-shackles at their ends in accordance with IS 4001: 1976 'Mine tubs (first revision)'. This standard has therefore been revised to modify the design of coupling. The design of drawbar of mine tubs has also been modified and is included in IS 8534 (Part 5): 1995.

Other important change involved in this revised version is the application of only one size of coupling for use upto a safe working load of 50 kN. Earlier three different sizes for 10, 20 and 30 kN safe working load were specified in this standard.

Couplings specified in this standard shall be used in conjunction with flat type (Type B) or plate type (Type C) drawbars specified in IS 8534 (Part 5): 1995.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

MINE TUB COUPLINGS AND DRAWBARS

PART 4 F-SHACKLE AND LINK TYPE

(First Revision)

1 SCOPE

This standard (Part 4) specifies the requirements of F-shackle and link type mine tub coupling used for connecting mine tubs in a set of tubs and having a maximum safe working load of 50 kN.

2 REFERENCES

The following Indian Standards are necessary adjuncts to this standard:

IS No.

Title

8534 Mine tub couplings and draw-(Part 1): 1994 bars: Part 1 General requirements (first revision)

8534 Mine tub couplings and draw-(Part 2): 1995 bars: Part 2 C-link and D-shackle type (first revision)

8534 Mine tub couplings and draw-(Part 3): 1995 bars: Part 3 R-shackle and link type (first revision)

3 DIMENSIONS

3.1 Assembly and Nomenclature — See Fig. 1.

3.2 F-shackle

3.2.1 For Straight Locking Arrangement — See Fig. 2.

3.2.2 For Taper Locking Arrangement — See Fig. 3.

3.3 Link and Locking Pins

Link and locking pins (both for straight locking arrangement as well as for taper locking arrangement) shall conform in all respect with IS 8534 (Part 3): 1995.

4 TOLERANCES

Tolerances on components of F-shackle and link type of coupling shall be as specified in 4 of IS 8534 (Part 2): 1995.

5 DESIGNATION

A mine tub coupling of F-shackle and link type with taper locking arrangement conforming to this standard shall be designated as:

Tub Coupling, F-shackle and Link, Taper, IS 8534 (Part 4)

6 GENERAL REQUIREMENTS

Mine tub couplings of F-shackle and link type shall conform in all respect with IS 8534 (Part 1): 1994.

7 MARKING

7.1 Each coupling and drawbar shall be permanently and legibly marked on a non-vital component with the following information:

- a) Manufacturer's identification mark;
- b) Safe working load in kN;
- c) Type of heat treatment, given; and
- d) Identification mark bearing with manufacturer's certificate of test examination [see Annex A of IS 8534 (Part 1): 1994].
- 7.1.1 The stamps used for marking shall be of 5 mm size. Care shall be taken that the indentation is neither too sharp nor excessive in depth.

7.2 BIS Certification Marking


7.2.1 The C-link and D-shackle type mine tub coupling may also be marked with the Standard Mark.

7.2.2 The use of the Standard Mark is governed by the provisions of Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.


N

All dimensions in millimetres.

Fig. 1 Assembly and Nomenclature



DETAIL OF BORE








Fig. 2 F-shackle for Straight Locking Arrangement



DETAIL OF BORE






Fig. 3 F-shackle for Taper Locking Arrangement

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards Monthly Addition'.

This Indian Standard has been developed from Doc: No. HMD 8 (0048).

LUCKNOW. PATNA. THIRUVANANTHPURAM.

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected
	BUREAU OF INDIAN STANDARD	S
Headquarters: Manak Bhavan, 9 Bahadur	Shah Zafar Marg, New Delhi 110002	
Telephones: 331 01 31, 3	31 13 75	Telegrams: Manaksanstha (Common to all Offices)
Regional Offices:		Telephone
Central: Manak Bhavan, NEW DELHI 11	9 Bahadur Shah Zafar Marg 0002	{331 01 31 {331 13 75
Eastern: 1/14 C. I. T. Sch CALCUTTA 700	eme VIII M, V. I. P. Road, Maniktola 0054	{37 84 99, 37 85 61 {37 86 26, 37 86 62
Northern: SCO 335-336, S	Sector 34-A, CHANDIGARH 160022	60 38 43, 60 20 25,
Southern: C. I. T. Campu	s, IV Cross Road, MADRAS 600113	{235 02 16, 235 04 42 {235 15 19, 235 23 15
Western: Manakalaya, E9	MIDC, Marol, Andheri (East)	632 92 95, 632 7 8 5 8
BOMBAY 40009	23	632 78 91, 632 78 9 2
FARIDABAD. (BANGALORE, BHOPAL, BHUBA GHAZIABAD, GUWAHATI, HYDER	NESHWAR. COIMBATORE. ABAD. JAIPUR. KANPUR